

# Y branch with PDF chart

www.fabricatorguide.com 22" x 22"									
NO:	B Branch pipe					H Header pipe			
CENTER LI	Y Branch 60°	Y Branch 45°	Y Branch 30°	Y Branch 22.5°	CENTER LI	Y Header 60°	Y Header 45°	Y Header 30°	Y Header 22.5°
L 1	541	425	224	136	C 1	700	700	700	800
L 2	544	430	233	149	C 2	669	677	685	789
L 3	553	446	260	187	C 3	639	656	671	779
L 4	568	471	304	248	C 4	611	636	659	769
L 5	587	505	363	331	C 5	587	619	647	761
L 6	611	547	435	431	C 6	568	605	638	754
L 7	639	594	517	546	C 7	553	594	632	749
L 8	669	646	607	670	C 8	544	588	627	746
L 9	700	700	700	800	C 9	541	586	626	745
L 10	669	677	685	789	C 10	544	588	627	746
L 11	639	656	671	779	C 11	553	594	632	749
L 12	611	636	659	769	C 12	568	605	638	754
L 13	587	619	647	761	C 13	587	619	647	761
L 14	568	605	638	754	C 14	611	636	659	769
L 15	553	594	632	749	C 15	639	656	671	779
L 16	544	588	627	746	C 16	669	677	685	789
L 17	541	586	626	745	C 17	700	700	700	800
L 18	544	588	627	746	C 18	669	677	685	789
L 19	553	594	632	749	C 19	639	656	671	779
L 20	568	605	638	754	C 20	611	636	659	769
L 21	587	619	647	761	C 21	587	619	647	761
L 22	611	636	659	769	C 22	568	605	638	754
L 23	639	656	671	779	C 23	553	594	632	749
L 24	669	677	685	789	C 24	544	588	627	746
L 25	700	700	700	800	C 25	541	586	626	745
L 26	669	646	607	670	C 26	544	588	627	746
L 27	639	594	517	546	C 27	553	594	632	749
L 28	611	547	435	431	C 28	568	605	638	754
L 29	587	505	363	331	C 29	587	619	647	761
L 30	568	471	304	248	C 30	611	636	659	769
L 31	553	446	260	187	C 31	639	656	671	779
L 32	544	430	233	149	C 32	669	677	685	789

