

<https://fabricatorguide.com>

one side miter cut pipe pdf chart 60° 45° 30° 22.5° 24 center line

20" pipe one side miter cut						22" pipe one side miter cut						24" pipe one side miter cut					
CENTER LINE	60° Deg-ree	45° Deg-ree	30° Deg-ree	22.5° Deg-ree	15° Deg-ree	CENTER LINE	60° Deg-ree	45° Deg-ree	30° Deg-ree	22.5° Deg-ree	15° Deg-ree	CENTER LINE	60° Deg-ree	45° Deg-ree	30° Deg-ree	22.5° Deg-ree	15° Deg-ree
C 1	50	50	50	50	50	C 1	50	50	50	50	50	C 1	50	50	50	50	50
C 2	65	58	55	53	52	C 2	66	59	55	53	52	C 2	68	60	56	54	52
C 3	108	84	69	64	59	C 3	114	87	71	65	60	C 3	120	90	73	66	60
C 4	178	124	92	80	69	C 4	191	131	97	83	71	C 4	204	139	101	87	73
C 5	269	177	123	102	84	C 5	291	189	130	107	87	C 5	313	202	138	113	90
C 6	376	238	158	128	100	C 6	408	257	169	135	105	C 6	441	275	180	143	110
C 7	489	304	196	155	118	C 7	533	329	211	165	124	C 7	577	354	226	176	131
C 8	603	369	234	182	135	C 8	659	401	253	195	144	C 8	714	433	271	208	152
C 9	709	431	270	207	152	C 9	775	469	291	223	162	C 9	841	507	313	239	172
C 10	801	483	300	229	166	C 10	876	526	325	247	177	C 10	951	570	350	265	189
C 11	870	523	323	246	177	C 11	953	571	351	265	189	C 11	1035	618	378	285	202
C 12	914	549	338	256	183	C 12	1001	599	367	277	197	C 12	1087	649	395	298	210
C 13	929	558	343	260	186	C 13	1017	608	372	281	199	C 13	1105	659	401	302	213
C 14	914	549	338	256	183	C 14	1001	599	367	277	197	C 14	1087	649	395	298	210
C 15	870	523	323	246	177	C 15	953	571	351	265	189	C 15	1035	618	378	285	202
C 16	801	483	300	229	166	C 16	876	526	325	247	177	C 16	951	570	350	265	189
C 17	709	431	270	207	152	C 17	775	469	291	223	162	C 17	841	507	313	239	172
C 18	603	369	234	182	135	C 18	659	401	253	195	144	C 18	714	433	271	208	152
C 19	489	304	196	155	118	C 19	533	329	211	165	124	C 19	577	354	226	176	131
C 20	376	238	158	128	100	C 20	408	257	169	135	105	C 20	441	275	180	143	110
C 21	269	177	123	102	84	C 21	291	189	130	107	87	C 21	313	202	138	113	90
C 22	178	124	92	80	69	C 22	191	131	97	83	71	C 22	204	139	101	87	73
C 23	108	84	69	64	59	C 23	114	87	71	65	60	C 23	120	90	73	66	60
C 24	65	58	55	53	52	C 24	66	59	55	53	52	C 24	68	60	56	54	52
26" pipe 1 side miter 24 center line						28" pipe 1 side miter 24 center line						30" pipe 1 side miter 24 center line					
	60°	45°	30°	22.5°	15°		60°	45°	30°	22.5°	15°		60°	45°	30°	22.5°	15°
C 1	50	50	50	50	50	C 1	50	50	50	50	50	C 1	50	50	50	50	50
C 2	69	61	56	54	53	C 2	71	62	57	55	53	C 2	72	63	57	55	53
C 3	126	94	75	68	61	C 3	132	97	77	69	62	C 3	138	101	79	71	63
C 4	217	146	105	90	75	C 4	230	154	110	93	77	C 4	243	161	114	96	79
C 5	335	215	145	118	94	C 5	357	227	152	123	97	C 5	379	240	160	128	101
C 6	473	294	191	151	115	C 6	506	313	202	159	120	C 6	539	332	213	166	125
C 7	621	380	240	186	138	C 7	665	405	255	197	145	C 7	709	431	269	207	152
C 8	769	465	290	222	161	C 8	825	497	308	235	169	C 8	880	529	326	248	178
C 9	907	545	335	255	182	C 9	973	583	357	270	192	C 9	1039	621	379	286	203
C 10	1026	613	375	283	201	C 10	1101	657	400	301	212	C 10	1176	700	425	319	224
C 11	1117	666	405	305	215	C 11	1199	713	433	324	227	C 11	1281	760	460	344	240
C 12	1174	699	424	318	223	C 12	1260	749	453	339	237	C 12	1347	799	482	360	250
C 13	1193	710	431	323	226	C 13	1281	761	460	344	240	C 13	1369	812	489	365	254
C 14	1174	699	424	318	223	C 14	1260	749	453	339	237	C 14	1347	799	482	360	250
C 15	1117	666	405	305	215	C 15	1199	713	433	324	227	C 15	1281	760	460	344	240
C 16	1026	613	375	283	201	C 16	1101	657	400	301	212	C 16	1176	700	425	319	224
C 17	907	545	335	255	182	C 17	973	583	357	235	192	C 17	1039	621	379	286	203
C 18	769	465	290	222	161	C 18	825	497	308	235	169	C 18	880	529	326	248	178
C 19	621	380	240	186	138	C 19	665	405	255	197	145	C 19	709	431	269	207	152
C 20	473	294	191	151	115	C 20	506	313	202	123	120	C 20	539	332	213	166	125
C 21	335	215	145	118	94	C 21	357	227	152	123	97	C 21	379	240	160	128	101
C 22	217	146	105	90	75	C 22	230	154	110	93	77	C 22	243	161	114	96	79
C 23	126	94	75	68	61	C 23	132	97	77	69	62	C 23	138	101	79	71	63
C 24	69	61	56	54	53	C 24	71	62	57	55	53	C 24	72	63	57	55	53