



Schedule SCH40 STD SCH80 XS XXS SCH120 SCH160

[www.fabricatorguide.com](http://www.fabricatorguide.com)

piping Eccentric reducer dimension in mm

Inch size	Ecc. H	Offset C	Inch size	Ecc. H	Offset C	Inch size	Ecc. H	Offset C	Inch size	Ecc. H	Offset C
¾ × ½	38.1	2.5	14 × 8	330.2	68	28 × 26	609.6	25.5	38 × 26	609.6	152
1 × ¾	50.8	3.5	14 × 6	330.2	93.5	28 × 24	609.6	51	40 × 38	609.6	25.5
1 × ½	50.8	6	16 × 14	355.6	25.5	28 × 20	609.6	101	40 × 36	609.6	51
1 ½ × 1	63.5	7.5	16 × 12	355.6	41	28 × 18	609.6	127	40 × 34	609.6	76.5
1 ½ × ¾	63.5	11	16 × 10	355.6	66.5	30 × 28	609.6	25.5	40 × 32	609.6	102
1 ½ × ½	63.5	13.5	16 × 8	355.6	93.5	30 × 26	609.5	51	40 × 30	609.6	127
2 × 1 ½	76.2	6	18 × 16	381	25.5	30 × 24	609.6	76.5	42 × 40	609.6	25
2 × 1	76.2	13.5	18 × 14	381	51	30 × 20	609.6	127	42 × 38	609.6	50.5
2 × ¾	76.2	17	18 × 12	381	67	32 × 30	609.6	25	42 × 36	609.6	76
3 × 2	88.9	14.3	18 × 10	381	92	32 × 28	609.6	50.5	42 × 34	609.6	101
3 × 1 ½	88.9	20	20 × 18	508	25.5	32 × 26	609.6	76	42 × 32	609.6	127
4 × 3	101.6	28	20 × 16	508	51	32 × 24	609.6	101	42 × 30	609.6	152
4 × 2	101.6	27	20 × 14	508	76.5	34 × 32	609.6	25.5	44 × 42	609.6	25.5
4 × 1 ½	101.6	33	20 × 12	508	92	34 × 30	609.6	50.5	44 × 40	609.6	50.5
6 × 4	139.7	27	22 × 20	508	25	34 × 26	609.6	101	44 × 38	609.6	76
6 × 3	139.7	39	22 × 18	508	50.5	34 × 24	609.6	127	44 × 36	609.6	101
8 × 6	152.4	25	22 × 16	508	76	36 × 34	609.6	25.5	46 × 44	711.2	25.5
8 × 4	152.4	52.5	22 × 14	508	101	36 × 32	609.6	51	46 × 42	711.2	51
10 × 8	177.8	27	24 × 22	508	25.5	36 × 30	609.6	76	46 × 40	711.2	76
10 × 6	177.8	52.5	24 × 20	508	25.8	36 × 26	609.6	127	46 × 38	711.2	101
10 × 4	177.8	79.5	24 × 18	508	76	36 × 24	609.6	152	48 × 46	711.2	25.5
12 × 10	203.2	25.4	24 × 16	508	101	38 × 36	609.6	25.5	48 × 44	711.2	51
12 × 8	203.2	52.4	26 × 24	609.6	25.5	38 × 34	609.6	51	48 × 42	711.2	76.5
12 × 6	203.2	77.5	26 × 22	609.6	51	38 × 32	609.6	76	48 × 40	711.2	101
14 × 12	330.2	16	26 × 20	609.6	76	38 × 30	609.6	101			
14 × 10	330.2	41	26 × 18	609.6	101.5	38 × 28	609.6	127			